



研 域
YENOTEK

STX-F41_2L VER:1.1A 规格表



STX-F41_2L VER:1.1A 正面图



STX-F41_2L VER:1.1A 后置 IO 图



STX-F41_2L VER:1.1A 前置 IO 图



STX-F41_2L VER:1.1A 侧面图



Product model	STX-F41_2L VER:1.1A(J4125)
processor	Integrated Intel® Celeron J4125 2.0GHz quad-core quad-thread processor, TDP 10W
	Compatible with the full range of Gemini Lake cpus
chipset	SOC
Internal memory	1* SODIMM slot for supporting DDR4 2400MHz memory and a maximum of 8GB
display	Integrated Intel® UHD Graphics 600 core graphics card
	1 x VGA port, 1 x HD OUTPUT port
	1* EDP interface
network	2* Realtek8111H Gigabit NIC, supporting network wake up and PXE functions
storage	1* M.2 slot, supporting the M.2 2280 SATA SSD
	1* SATA 3.0 hard disk interface, SATA interface transmission speed up to 6Gbps
Tone frequency	Onboard ALC897 7.1+2 high fidelity audio controller, support Mic, Line out, power amplifier
	Power amplifier supports 4 Ω 3W speakers
Expansion slot	The 1* M.2 slot supports the M.2 2230 WiFi module
I/O ports on the rear panel	1* DC12V power input port
	1* HD OUTPUT port
	1 x VGA port
	2* RJ45 Gigabit network port (USB3 and LAN2 can be selected as one gigabit network port)
	1* Line out, 1*Mic



I/O ports on the front panel	4* USB3.0 port 1*PS/2 keyboard and mouse 2-in-1 seat cell 1* Power switch 1* Power indicator 1* hard disk indicator
Built-in I/O interface	1* EDP interface, 2*15pin row pin 1*JVGA port, 1*12pin and DB15 are the same signal 1* USB2.0 port 1*5pin (F_USB1 supports only one USB) 2* USB2.0 interface 2*5pin 1* RS232 serial port 2*5pin 1* power amplifier interface 1*4pin 1* hard drive power port 1*4pin 1* Front panel function button and indicator port 2*5pin 1* DC 12v power port 1*4pin
Fan interface	1*4pin CPU intelligent fan interface
GPIO	Supports four input/output GPIO
BIOS	64Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 10/Linux
Power supply type	Adopts DC 12V power supply
Operating temperature	-10°C to 60°C
Storage temperature	-20°C to 70°C
Working humidity	5%-95% relative humidity, no condensation
dimension	120mm x 120mm



研 域
YENOTEK

订购信息：

No	Model	Processor	Frequency	Memory	VGA	HD OUTPUT	LVDS	EDP	LAN	USB	COM	RS485/422	Power
1	STX-F41_1L VER:1.1(J4105)	J4125	1.5G	1*SODDR4	1	1	/	1	1*8111H	7	1	/	DC12V
2	STX-F41_2L VER:1.1(J4125)	J4125	2.0G	1*SODDR4	1	1	/	1	2*8111H	7	1	/	DC12V