


STX-N29_2L VER1.6 规格表



STX-N29_2L VER:1.6 主板正面图



STX-N29_2L VER:1.6 主板背面 IO 图



STX-N29_2L VER:1.6 主板正面 IO 图



STX-N29_2L VER:1.6 主板侧面图

Product number	STX-N29_2L VER:1.6
processor	Integrated Intel®J1900/2.00GHz quad-core processor, TDP power consumption 10W
chipset	Based on Intel® Bay trail SOC platform
RAM	1*SO DDRIII slot, only supports 1600/1333MHz DDR3L/1.35V memory, maximum support 8GB
Show	Integrated Intel®HD Graphics core graphics 1*VGA, 1*HDMI, 1*LVDS interface (support dual channel 24BIT) Support VGA; HDMI; LVDS synchronous/asynchronous display
The internet	2* RTL8111F Gigabit Ethernet chip, support Wake on LAN/PXE function
Store	1* SATA hard disk interface
Audio	Onboard ALC662 6-channel high-fidelity audio controller, support MIC/Line-out. The power amplifier recommends using 2 Ω 5W speakers
Expansion slot	1* Mini-PCIE slot supports WIFI/3G module 1* MSATA slot supports SSD/WIFI, SSD transmission speed up to 3Gbps
Backplane I/O interface	1*USB2.0, 1*USB3.0 1* HDMI port 1* VGA port 2* RJ-45 network interface 1* Line out (green), 1* MIC (purple) 1* RJ-45 serial port 1* Power button 1* 12V DC_JACK input
Built-in I/O interface	1* LVDS interface (2*15pin), support dual channel 24BIT LCD display 1* LVDS backlight interface 1*6pin) 1* JVGA1 interface (1*12pin) same signal as DB15 1* RS232 serial port 2* USB2.0 interface (2*5pin)

	1* PS/2 mouse keyboard interface (1*6Pin)
	1* Front panel audio interface (2*5pin)
	1* SIM card holder
	1* Hard disk power supply interface
	1* Front panel function button and indicator light interface (2*5pin)
	1* 4pin ATX 12V input and output power interface
	1* Amplifier interface (1*4pin)
Fan interface	1* CPU fan interface 4pin
GPIO	Support 4 input and output GPIO
BIOS	AMI 64Mb Flash ROM
Watchdog	Support hardware reset function (256 levels, 0~255 seconds)
operating system	Windows 7/Windows 10/Linux
Power type	DC_12V single power input
Operating temperature	-10°C ~ 60°C
Storage temperature	-20°C ~ 70°C
Working humidity	5%-95% relative humidity, non-condensing
Size	120mm x 120mm

订购信息:

No.	Mode	Processor	Frequency	Memory	VGA	HDMI	LVDS	LAN	USB	COM	Power
1	STX-N29_2L VER:1.6	J1900	2.0G	1*SODDDR3L	1	1	2ch/24BIT	2	4	2	DC/12V
2	STX-N29 VER:1.6	J1900	2.00G	1*SODDDR3L	1	1	X	1	6	2	DC/12V
3	STX-N29_1L VER:1.6	J1900	2.0G	1*SODDDR3L	1	1	2ch/24BIT	1	6	2	DC/12V



深圳市汉智星科技有限公司